

2G11 series



Energy saving and environmental protection

RD-2G11-225-10W

Real Power	10W
Light Source	2835 SMD
Lumen	1000Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC

Icons: Dimmable, Ra > 80, Energy Saving, Long Life

RD-2G11-320-13W

Real Power	13W
Light Source	2835 SMD
Lumen	1300Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC

Icons: Dimmable, Ra > 80, Energy Saving, Long Life

RD-2G11-410-15W

Real Power	15W
Light Source	2835 SMD
Lumen	1500Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC

Icons: Dimmable, Ra > 80, Energy Saving, Long Life

RD-2G11-535-20W

Real Power	20W
Light Source	2835 SMD
Lumen	2000Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC

Icons: Dimmable, Ra > 80, Energy Saving, Long Life

RD-ALY7-10W

Real Power	10W
Light Source	94 pcs 2835
Lumen	1000Lm
Color Temperature	2700-6500K
CRI	Ra>80
Voltage	120/230V AC

Icons: Dimmable, Ra > 80, Energy Saving, Long Life

RD-E26-CP-8W

Real Power	8W
Light Source	SMD
Lumen	1020Lm
Color Temperature	3000/4000K
Beam Angle	300°
Material	Ceramic+PC
CRI	Ra>80
Voltage	120V AC

Icons: Dimmable, Ra > 80, Energy Saving, Long Life

Attention:

- Lifespan of the bulbs will be effected while working ambient temperature that higher 45°C/113°F.
- The inner space of enclosed fixtures should be 5 times bigger than the size of the bulbs.
- The dimming level for dimmable products would be under a certain dimmer, it is better to take samples for testing the dimming function.